

Surface Mount Ceiling Light

SMART & COST EFFECTIVE

SAVE LABOUR

- · Less number of lights
- Less integration work

BRIGHT & EFFICIENT

- Highly efficient LED chips
- Built-in microwave control
- Built-in battery backup

Proven Technology

Battery Backup & RF Microwave Control working together.









Specifications:

Power: 15W18W/24W

 CCT:
 6500K

 Beam Angle:
 160°

 Protection:
 IP20

Specifications:

Voltage: 220VAC – 240VAC

Frequency: 50Hz

Lumen Efficiency: 80-120 lm/w

CRI: 85%

Light Source Life: 50,000 hrs

Options:

Microwave Sensor Control:


Detection Range: 2.7-5.5m

Max Installation Height: 6m

Time delay: 45s

25s - 60s on special requesst

Steps: 100% & 20%



Battery Backup:

Duration: > 2hrs

Battery Type: LiFePO4

Backup Load: Full Power

For Industrial Use Only

Ordering Information

Description

SURFACE MOUNT ROUND CEILING/WALL LIGHT(15W, 6500K)
SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH BATTERY BACKUP(15W, 6500K) PIKA-SR-X-15-6500K PIKA-SRB-X-15-6500K PIKA-SRR-X-15-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH MICROWAVE CONTROL (15W, 6500K) SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH BATTERY BACKUP AND MICROWAVE CONTROL (15W, 6500K) PIKA-SRBR-X-15-6500K PIKA-SR-X-18-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT(18W, 6500K) PIKA-SRB-X-18-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH BATTERY BACKUP(18W, 6500K) PIKA-SRR-X-18-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH MICROWAVE CONTROL (18W, 6500K) PIKA-SRBR-X-18-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH BATTERY BACKUP AND MICROWAVE CONTROL(18W, 6500K) PIKA-SR-X-24-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT(24W, 6500K) PIKA-SRB-X-24-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH BATTERY BACKUP(24W, 6500K) SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH MICROWAVE CONTROL (24W, 6500K) PIKA-SRR-X-24-6500K PIKA-SRBR-X-24-6500K SURFACE MOUNT ROUND CEILING/WALL LIGHT WITH BATTERY BACKUP AND MICROWAVE CONTROL (24W, 6500K)

Part No.