

Ultra Slim LED Panel Light

SMART & COST EFFECTIVE

SAVE LABOUR

- Less number of lights
- Less integration work

BRIGHT & FFFICIENT

- Highly efficient LED chips
- Built-in microwave
 control
- Built-in battery backup

Proven Technology

Battery Backup & RF Microwave Control working together.









Specifications:

Power: 12W/15W/18W

 Size:
 6'/7'/8'

 CCT:
 6500K

 Beam Angle:
 160°

 Protection:
 IP20

Note: It is recommended to install the

Backup Supply and the battery in a

junction box

Specifications:

Voltage: 220VAC – 240VAC

Frequency: 50Hz PF: > 0.9

Lumen Efficiency: 80-120 lm/w

CRI: 85% Light Source Life: 50,000 hrs

Options:

Microwave Sensor Control:


Detection Range: 2.7-5.5m

Max Installation Height: 6m

Time delay: 45s

25s - 60s on special requesst

Steps: 100% & 20%



Battery Backup:

Duration: > 2hrs

Battery Type: LiFePO4

Backup Load: Full Power

Ordering Information

For Industrial Use Only

Part No. **Description** RECESSED ROUND PANEL LIGHT(6', 12W, 6500K) RECESSED ROUND PANEL LIGHT WITH BATTERY BACKUP(6', 12W, 6500K) PIKA-RR-6-12-6500K PIKA-RRB-6-12-6500K RECESSED ROUND PANEL LIGHT WITH MICROWAVE CONTROL(6', 12W, 6500K) RECESSED ROUND PANEL LIGHT WITH BATTERY BACKUP AND MICROWAVE CONTROL(6', 12W, 6500K) PIKA-RRR-6-12-6500K PIKA-RRBR-6-12-6500K PIKA-RR-7-15-6500K RECESSED ROUND PANEL LIGHT(7', 15W, 6500K) PIKA-RRB-7-15-6500K RECESSED ROUND PANEL LIGHT WITH BATTERY BACKUP(7', 15W, 6500K) PIKA-RRR-7-15-6500K RECESSED ROUND PANEL LIGHT WITH MICROWAVE CONTROL (7', 15W, 6500K) PIKA-RRBR-7-15-6500K RECESSED ROUND PANEL LIGHT WITH BATTERY BACKUP AND MICROWAVE CONTROL (7', 15W, 6500K) PIKA-RR-8-18-6500K RECESSED ROUND PANEL LIGHT(8', 18W, 6500K) PIKA-RRB-8-18-6500K RECESSED ROUND PANEL LIGHT WITH BATTERY BACKUP(8', 18W, 6500K) RECESSED ROUND PANEL LIGHT WITH MICROWAVE CONTROL(8', 18W, 6500K) RECESSED ROUND PANEL LIGHT WITH BATTERY BACKUP AND MICROWAVE CONTROL(8', 18W, 6500K) PIKA-RRR-8-18-6500K PIKA-RRBR-8-18-6500K